

## Symmetrical reduction fittings with copper alloy locks



**Product features:**

Matière: Copper alloys

Connection type: Reduction fitting

Reference: -

EAN13: -

DN Sym1: 40, 50, 65, 80, 100

DN Sym2: 20, 25, 40, 50, 65, 80

## Symmetrical reduction fittings with copper alloy locks

Guillemain's NF E 29-572 PN16 copper-alloy fitting is designed to provide a reliable and secure connection in piping systems. This specific model is a symmetrical reduction fitting equipped with locks, enabling leak-free fastening. The copper alloy ensures high corrosion resistance and exceptional durability, making this product ideal for applications requiring long service life and enhanced reliability.

This fitting complies with NF E 29-572 standards, guaranteeing its quality and conformity to the most demanding industrial standards. It is perfect for installations in a variety of sectors, including hydraulic and pneumatic systems.

### Features :

- **Material:** High-grade copper alloy

- **Standard:** NF E 29-572
- **Pressure rating:** PN16 (16 bar)
- **Type:** Symmetrical reduction fitting
- **Locks :** Equipped with locks for secure fastening
- **Application:** Suitable for piping, hydraulic and pneumatic installations
- **Dimensions:** Available in various sizes to suit system requirements
- **Durability:** Excellent resistance to corrosion and high temperatures
- **Ease of installation:** Quick and easy connection, no leaks

## Advantages of symmetrical fittings with locks :

1. **Maximum safety:** Thanks to its locking system, this fitting guarantees installation without the risk of leakage or accidental disconnection.
2. **Long service life:** The copper alloy used in its manufacture provides excellent corrosion resistance, ensuring long service life even in harsh environments.
3. **Quality standard:** Conforms to NF E 29-572, ensuring optimum performance and reliability.
4. **Ease of maintenance:** Easy-to-clean design reduces maintenance costs.
5. **Versatility of application:** Ideal for installations in a variety of sectors, including plumbing, heating and other piping systems.

## Application:

This Guillemain fitting is particularly useful in systems where safety and longevity are paramount. It is designed for use in environments where leakage must be avoided at all costs, such as in plumbing, hydraulic or pneumatic systems. Its symmetrical design and locking system enable fast, efficient installation, with an operating pressure of 16 bar. What's more, the material's resistance to chemical aggression and high temperatures makes it a preferred choice for demanding systems.

Guillemain's NF E 29-572 PN16 copper alloy fitting with locks is a top-quality product, offering a secure, durable and reliable solution for your piping needs. It guarantees optimum performance, leak-free installation and impressive longevity. For more information on this product, or to place an order, please contact **MMF Protection et Sécurité**, who will be delighted to assist you with your projects.