

## Half DSP and AR lockshield female threaded sleeve PN25 aluminum



**Product features:**

Material: Aluminum

Connection type: Half-connector

Socket: Female

Reference: -

EAN13: -

Female thread diameter / inlet: 1"1/4, 1"1/2,  
2", 3", 2"1/2, 4"

DSP/AR symmetrical diameter: 40, 65, 100

### DSP and AR locking half-fitting female threaded sleeve PN25 aluminum

The **symmetrical DSP and AR NF S 61-701 PN25 coupling** is a **locking** half-fitting designed for fast, secure connection of fire hoses. Made from **high-quality aluminum**, it features a **female threaded bushing** guaranteeing increased resistance to pressure(**PN25**). This fitting complies with current standards, offering optimum reliability for fire safety professionals.

### Features :

- **Type:** DSP and AR half coupling with lock

- **Standard:** NF S 61-701
- **Material:** Robust, lightweight aluminum
- **Thread:** Female threaded sleeve
- **Pressure rating:** PN25
- **Application:** Fast, safe connection of fire hoses

## Advantages of a DSP and ARhalf-connector with locking female threaded sleeve PN25 aluminum :

**High strength:** Designed to withstand pressures of up to **25 bar**, ensuring a perfect seal.

**Norme NF S 61-701:** Guarantee of quality and compliance with fire safety requirements.

**Quick connection:** Locking system for efficient, reliable connection in emergency situations.

**Durable material:** Aluminum offers excellent corrosion resistance and long service life.

**Versatility:** Compatible with standardized equipment used by firefighters and fire protection professionals.

## Application:

The symmetrical DSP and AR **NF S 61-701 PN25** coupling is **essential equipment for fire-fighting services**, industry and local authorities. It facilitates the **connection of hoses**, guaranteeing **fast, effective intervention** in an emergency. Its locking system ensures a **tight, secure** connection, reducing the risk of leakage.

If you're looking for a reliable, standards-compliant connection for your fire-fighting equipment, the **symmetrical DSP and AR NF S 61-701 PN25** aluminum **fitting** is the ideal solution.

**MMF Protection et Sécurité** offers you this quality product. **Contact us for more information** and benefit from the expertise of our fire protection professionals.