

## Flashlight PELI™ STEALTHLITE™ 2410Z0 ATEX ZONE 0



Reference: -  
EAN13: -

Color: Yellow

### Product features:

Power category: From 101 to 200 lumens  
ATEX certification: Zone 0  
Power supply: Batteries  
Autonomy indicator: No  
Lighting mode: On / Off  
Light output: 153 lms  
Beam range: 165 m  
Waterproofing: IPX7  
Length: 17.8 cm  
Weight with batteries: 207 g  
Battery type: LR06  
Number of batteries: 4  
Batteries included: No  
Autonomie.: 5h45  
Refillable: No

### ATEX Zone 0 StealthLite™ Peli™ 2410Z0 flashlight - Performance and safety

The [ATEX Zone 0 StealthLite™ Peli™ 2410Z0 flashlight](#) is a high-performance model, offering 153 lumens of light output. Designed with advanced LED technology, it emits a collimated beam, guaranteeing powerful, concentrated illumination, ideal for demanding environments.

Rated ATEX Zone 0, this lamp is specially designed for hazardous areas, offering maximum safety thanks to its explosion-proof features. With an IPX7 protection rating, it is also waterproof, making it perfectly suited to wet or harsh conditions.

Powered by 4 AA LR06 batteries, the StealthLite™ 2410Z0 measures 17.8 cm in length and weighs 207 g, offering easy grip and stress-free transport. The side switch provides instant illumination, while its unbreakable ABS resin body and impact-resistant polycarbonate lens ensure exceptional durability. ATEX-compliant, this flashlight is a safe and reliable solution for any operation in hazardous environments.

### StealthLite™ Peli™ LED 2410Z0 torch features:

The **ATEX zone 0 StealthLite™ Peli™ 2410Z0 flashlight** is the essential tool for professionals operating in hazardous environments. Designed to meet the strictest safety standards, it combines performance and robustness.

With an impressive range of 165 meters, this lamp enables you to effectively illuminate dark, hard-to-reach areas. Its luminous intensity of 6,837 candelas guarantees exceptional visibility, even in the most extreme conditions. Thanks to its lighting power of 153 lumens, the **StealthLite™** perfectly illuminates workspaces, ensuring optimum safety in explosive areas.

The 5-hour, 45-minute battery life is a major plus, enabling users to benefit from constant illumination throughout their day. Its rugged, impact-resistant design makes it suitable for intensive use in the field, while providing effective protection against the risk of explosion.

The **StealthLite™ Peli™ 2410Z0** flashlight is a reliable ally for anyone working in demanding environments, where safety and visibility are essential. With this torch, you can work with confidence, even in the most critical situations.

- **Beam range:** 165 m with a luminous intensity of 6,837 candelas.
- **Autonomy:** 5 h 45 of continuous lighting, perfect for long working days.

## Advantages of the StealthLite™ Peli™ LED 2410Z0 torch:

The **ATEX** zone 0 StealthLite™ Peli™ 2410Z0 **flashlight** is an essential ally for those operating in hazardous environments. Designed to guarantee safety and efficiency, this lamp offers many advantages that make it a preferred choice.

Its ergonomic switch allows one-handed ignition, ensuring safe use even in critical situations. This feature is essential for professionals who need to keep their hands free while ensuring optimum lighting.

What's more, its IPX7 protection rating guarantees waterproofing, allowing use in rainy or damp conditions without fear of damage.

- **Practical ignition:** side switch designed for one-handed ignition, for ease of use.
- **Robust design:** Unbreakable ABS resin body and impact-resistant polycarbonate lens for maximum protection.
- **Safety certification:** ATEX zone 0 and IPX7 certified, guaranteeing safe use in hazardous environments.
- **Resistance to the elements:** Withstands extreme temperatures and corrosion, suitable for harsh conditions.

## Certification and standards

- **ATEX certification:** CE Ex II 1 G Ex ia IIC T4 Ga (gas) **and** CE Ex II 1 D Ex ia IIIC T135°C Da (dust)
- **Manufacturer's reference:** 2410-060-241E
- **Customs code:** 85131000
- **EAN:** 19428130701