

Angled flashlight PELI™ 3610Z0 Atex Zone 0



Product features:

Power category: From 101 to 200 lumens

ATEX certification: Zone 0

Power supply: Batteries

Autonomy indicator: No

Lighting mode: On / Off

Light output: 153 lms

Beam range: 165 m

Waterproofing: IPX7

Length: 19.1 cm

Weight with batteries: 298 g

Battery type: LR06

Number of batteries: 4

Batteries included: No

Autonomie.: 5h45

Refillable: No

Reference: -

EAN13: -

Color: Yellow

Peli™ 3610Z0 ATEX Zone 0 flashlight - Performance and safety

The Peli™ 3610Z0ATEX Zone 0 angled lamp is an **explosion-proof flashlight**, designed for use in explosive environments. With a **power output of 153 lumens and a light weight of 298 g**, it offers an excellent lumens-to-weight ratio among lamps in its category. Practical and secure, this lamp is equipped with a clamp for portable, hands-free lighting, ideal for professionals on the job.

Powered by 4 LR06 batteries, the Peli™ 3610Z0 boasts **ATEX** zone 0 (category 1) **certification** and IPX7 protection, guaranteeing optimum waterproofing. Made from ABS resin, it resists powerful impacts and is designed to cope with corrosion and extreme temperatures. All in all, this flashlight is a true ally for safe, effective lighting in the most demanding environments.

Features :

- **Lighting technology:** Equipped with Deep Mount LED technology, it offers a light output of 153 lumens and illuminates up to 165 m.
- **Operating time:** 4 LR06 batteries for a maximum operating time of 5 h 45.
- **Protection rating:** IPX7 (waterproof).
- **Body material:** Impact and corrosion-resistant ABS resin.
- **Power supply:** Operates on 4 LR06 batteries.

Advantages:

The Peli™ 3610Z0 features a slim, practical design, ideal for effective lighting in confined working environments. Thanks to its robust construction and ATEX certification, it **guarantees optimum safety** in hazardous areas. The stainless steel clamp allows easy and secure installation, providing a lighting solution where other LED flashlights cannot reach. Its brightness and reliability make it an indispensable tool for professionals operating in difficult conditions.

Certification and standards :

- **ATEX certification:** CE Ex II 1 G Ex ia IIC T4 Ga (gas) **and** CE Ex II 1 D Ex ia IIIC T135°C Da (dust)
- **Manufacturer's reference:** 3610-060-241E
- **Customs code:** 85131000
- **EAN:** 19428130749