

## Spotlight PELI™ 9415Z0 ATEX ZONE 0 RECHARGEABLE



Reference: -

EAN13: -

Color: Yellow

### Product features:

Power category: From 201 to 400 lumens

ATEX certification: Zone 0

Power supply: Battery

Autonomy indicator: Yes

Lighting modes: High - Low - Flashing

Light output: fort : 530 lumens / faible : 202 lumens

Beam range: fort : 272m / faible : 166m

Waterproofing: IPX4

Length: 22.2 cm

Weight with batteries: 1650 gr

Battery type: NiMH battery

Number of batteries: 4

Batteries included: Yes

Autonomy: 4:30 / 11:30 a.m

Refillable: Yes

**The Peli™ 9415Z0 floodlight** combines power, lightness and safety, making it an indispensable tool for professionals working in high-risk environments. Thanks to its advanced technology and safety certifications, this LED floodlight is perfectly suited to the most demanding work areas, such as those subject to explosive atmospheres.

The **Peli™ 9415Z0** is a compact yet powerful floodlight, equipped with four latest-generation LEDs and powered by Ni-MH batteries. Its robust, antistatic design guarantees not only a long service life but also optimum performance in extreme conditions. With a luminous range of 272 meters and 530 lumens of illumination, it ensures quality visibility, even in the most challenging conditions.

### Features:

- **Weight:** 1.4 kg (weight with batteries 1.65 kg)
- **Length:** 22.2 cm
- **Bulb type:** High-performance LED
- **Lighting modes**
  - High intensity
  - Low intensity
  - Flashing
- **Lighting range:** 272 meters
- **Lumens:** 530
- **Batteries**
  - Type: Ni-MH
  - Number of batteries: 4

- Battery size: C
- Rechargeable: Yes
- Charging time: 15 hours
- Battery level indicator: RGB LED
- **Materials**
  - Body: Anti-static Impact Modified PC/PBT
  - O-ring: EPDM
  - Lens: Anti-static, treated polycarbonate (PC)
- **Switch:** Push Button
- **Certifications**
  - IECEx ia
  - ATEX Zone 0 (Category 1)

## Benefits:

- **Increased safety:** The **Peli™ 9415Z0** is certified for use in the most sensitive environments, with IECEx ia and ATEX Zone 0 certifications. These labels ensure that the headlamp is perfectly suited to work areas classified as potentially explosive.
- **Advanced technology:** Thanks to its four powerful LEDs and latest-generation Ni-MH batteries, this floodlight offers intense brightness (530 lumens) and an impressive range of 272 meters, while being energy-efficient.
- **Lightweight and compact:** weighing just 1.4 kg and measuring just 22.2 cm in length, this torch is extremely practical to carry and use, offering an excellent compromise between size and power.
- **Durability and robustness:** construction in impact-resistant and anti-static materials guarantees a long service life, even in tough working conditions.

## Usability:

The **Peli™ 9415Z0 floodlight** is ideal for **professionals** in sectors such as the chemical industry, oil and gas, or maintenance in **environments where safety is paramount**. It is particularly recommended for operations in **ATEX** (potentially explosive areas) **classified zones**, as well as for interventions in **confined** or **low-visibility spaces**. Its **robustness** and **certification** make it a preferred choice for those requiring **reliable, safe** lighting in **extreme conditions**.

The **Peli™ 9415Z0 floodlight** represents the perfect balance between **power, safety** and **durability**. With its **ATEX Zone 0 certification** and **cutting-edge technologies**, it meets the requirements of professionals working in **high-risk environments**. **Compact, lightweight** and offering **impressive autonomy**, it's an indispensable tool for ensuring **optimum** lighting in the most demanding conditions. Whether you're on a mission in a **volatile** zone or in **difficult** working conditions, the Peli 9415Z0 will meet your needs **efficiently** and **safely**.