

Flashlight PELI™ 1930 ATEX ZONE 0



Reference: -EAN13: -

Color: Grey

Product features:

Power category: - 100 lumens ATEX certification: Zone 0 Power supply: Batteries Autonomy indicator: No Lighting mode: On / Off Light output: Fort : 12 lumens Beam range: Fort : 17m Waterproofing: IPX4 Length: 6.7 cm

Weight with batteries: 26gr Battery type: CR123 Lithium

Battery type: LR44 Number of batteries: 4 Batteries included: Yes Autonomie.: 4h15 Refillable: No

L1 1930Z0 torch - Reliable and compact

Discover the L1 1930Z0 torch, an ideal choice for those looking for a reliable, compact light source. Just 6.7 cm long and weighing just 26 g, it slips easily into a pocket or bag. Its polycarbonate body makes it exceptionally resistant to chemicals, water and corrosion, making it perfect for a variety of conditions.

L1 1930Z0 torch features

Product details:

- Dimensions: 6.7 cm long, weighs 26 g, slips easily into a pocket or bag.
- Material: Polycarbonate body, resistant to chemicals, water and corrosion.
- Waterproofing: IPX7-rated, waterproof for outdoor use even in the rain.

Accessories included:

- Neck cord
- Night vision discs for added convenience.
- 4 LR44 1.5 V alkaline batteries, providing a voltage of 6 V.

Advantages of the 1930Z0 flashlight



In the professional world, the L1 1930Z0 Peli[™] is an indispensable tool. Its ATEX Zone 0 certification allows safe use in potentially explosive atmospheres, which is crucial for sectors such as the chemical or oil industries. Its robust polycarbonate construction resists impact and corrosion, guaranteeing reliability even in harsh conditions. Lightweight and compact, this model is easy to transport, providing a light source that's always close at hand. With its LED bulb providing intense, long-lasting light, the L1 1930Z0 is perfectly suited to inspections, maintenance and emergency response.

- Compact and lightweight: 26 g
- Resistant to the elements: resistant to chemicals, water and corrosion, making it ideal for use in harsh environments.
- Efficient Lighting: Equipped with an LED bulb, it offers powerful, long-lasting light, perfect for a variety of applications.
- Convenient power supply: Operates on standard batteries (LR44), easy to replace, offering a stable voltage of 6 V.

ATEX certification: CE Ex II 1 G Ex ia op is IIC T6/T4 Ga (gas)