

## Half coupling with lock male aluminum threaded sleeve



**Product features:**

Matière: Aluminum

Connection type: Half-connector

Filetage: Male

Reference: -  
EAN13: -

DN Sym: 25, 40, 50, 65, 80, 100, 150  
Diamètre Mâle: 1", 1"1/2, 2", 2"1/2, 3", 4", 6"

## Half coupling with lock male threaded sleeve aluminum

The Guillemin aluminum half-coupling is an essential piece of equipment for ensuring safe, fast connections between hoses and industrial equipment. Compliant with **NF E 29-572 PN16** and **EN 14420-8** standards, this locking half-coupling with male threaded sleeve is designed to guarantee optimum sealing and increased robustness.

Made from high-quality aluminum, this fitting is appreciated for its lightness and resistance to corrosion. It is ideal for transferring liquids, powders or other substances in a variety of industrial sectors.

### Features :

- **Material:** robust, lightweight aluminum
- **Standards:** NF E 29-572 PN16 and EN 14420-8
- **Type:** Half lockshield
- **Thread:** Male

- **Strength:** Excellent mechanical strength and impact resistance
- **Use:** Suitable for industrial, agricultural and chemical applications
- **Tightness:** Designed for reliable connection

## Advantages of a locking half-fitting with male aluminum threaded sleeve :

**Safety and reliability:** Effective locking to prevent accidental disconnection.

**Ease of installation:** Quick and easy to install.

**Durability:** Resists extreme conditions and corrosion.

**Standards and compliance:** Ensures perfect compatibility with standardized equipment.

**Versatility:** Suitable for a wide range of industrial applications.

## Application:

The Guillemin aluminum half-fitting is mainly used in the following sectors:

- **Industrial:** Transport of liquids and powders in hydraulic and pneumatic circuits.
- **Chemical:** Safe handling of chemical products.
- **Agricultural:** Connection of hoses for irrigation and transport of agricultural products.
- **Fluid transport:** Suitable for applications requiring a fast, reliable connection.

This Guillemin aluminum half-fitting, compliant with NF E 29-572 PN16 and EN 14420-8 standards, is the solution of choice for safe, efficient connections in a variety of industrial applications.

**MMF Protection et Sécurité** guillemin offers you this product with a quality guarantee and personalized support. For more information or a quotation, **contact MMF today!**