

## Flashlight PELI™ 3315Z0 ATEX ZONE 0



Reference: -  
EAN13: -

Color: Yellow

### Product features:

Power category: From 101 to 200 lumens  
ATEX certification: Zone 0  
Power supply: Batteries  
Autonomy indicator: No  
Lighting mode: On / Off  
Light output: 138 lms  
Beam range: 146 m  
Waterproofing: IP67  
Length: 15.6 cm  
Weight with batteries: 176 g  
Battery type: LR06  
Number of batteries: 3  
Batteries included: Yes  
Autonomie.: Faisceau moyen : 11h à 20h  
Refillable: No

### The Peli™ 3315Z0 ATEX Zone 0 flashlight

The **Peli™ 3315Z0 ATEX Zone 0 flashlight** is designed for use in hazardous environments. Made of unbreakable ABS, it features a lockable battery compartment for maximum safety. Its unique LED, protected by a shockproof polycarbonate lens, provides a powerful light with a 19-hour runtime on three LR06 batteries

**ATEX Cat. 1 certified**, this lamp guarantees static-free operation.

Lightweight, robust and compact, it is suitable for handling with or without gloves, making it an indispensable tool for professionals in sensitive areas.

### Features of the Peli™ 3315Z0 ATEX Zone 0 torch

The Peli™ 3315Z0 ATEX Zone 0 flashlight is equipped with a unique LED that generates :

- a light output of 138 lumens,
- a beam reaching 146 meters,
- a maximum intensity of 5350 candelas.

With an operating time of 19 hours, it requires only three LR06 non-rechargeable batteries. Weighing just 176 grams, this lamp slips easily into a pocket. Its compact dimensions (15.6 cm long) ensure easy handling and protection. The body design ensures a comfortable grip, and the hand strap frees the hands easily.

### Advantages of the Peli™ 3315Z0 ATEX Zone 0 torch

The ATEX Zone 0 torch is the ideal portable spotlight for a variety of professional environments, such as:

- construction sites,
- security (firefighters, law enforcement and military),
- industry,
- cleaning,
- roads and traffic,
- railways.

Versatile, it can easily be converted into an efficient helmet lamp thanks to its optional brackets.

ATEX Zone 0 certified for dust and gases, it stands out for its robustness and benefits from the Peli™ guarantee of excellence.

## Certifications and standards:

- **ATEX certification:** CE Ex II 1 G Ex ia op is IIC T4 Ga and CE Ex II 1 D Ex ia IIIC T135°C Da
- **Manufacturer's reference:** 033150-0102-241E
- **Customs code:** 85131000
- **EAN:** 19428135010