

Flashlight PELI™ 3415MZ0 ATEX ZONE 0



Product features:

Power category: From 201 to 400 lumens

ATEX certification: Zone 0

Power supply: Batteries

Autonomy indicator: No

Lighting modes: Remote / near / both / flashing

Light output: 185 / 174 / 329 lumens

Beam range: 134 m / 38 m / 133 m

Waterproofing: IPX8

Length: 18.9 cm

Weight with batteries: 272 g

Battery type: LR06

Number of batteries: 3

Batteries included: No

Autonomy: 6 a.m. to 3 p.m

Refillable: No

Reference: -

EAN13: 0019428178659

Color: Yellow

The Peli™ 3415MZ0 ATEX angled flashlight

The **Peli™ 3415MZ0 ATEX Zone 0** angled flashlight stands out for its reliability, power and ease of use. Ideal for work in **ATEX zones**, the Peli™ 3415 provides powerful, safe lighting. Its pivoting head allows you to direct the beam according to your needs. Featuring beam and spot lighting technology, it offers the option of using these two modes independently or simultaneously. A side-mounted button selects spotlight, beam or a combination of the two.

Designed for extreme conditions, this lamp is **ATEX-certified** and waterproof to IPX8. Its powerful LED lighting rivals that of a spotlight, and thanks to its integrated magnet, it attaches easily to any metal surface.

Features of the Peli™ 3415MZ0 angled flashlight

The Peli™ 3415M0 ATEX Zone 0 torches are all-rounders par excellence. The Peli™ 3415MZ0 angled torch, 18.9 cm long and weighing 272 g, is made of antistatic polycarbonate, ATEX-certified and waterproof. Designed to make your work easier, this flashlight meets your needs with efficiency.

- Color: neon yellow
- Accessories included: 3 AAA batteries and wrist strap

Flashlight lighting modes :

- Spot: remote lighting, 185 lumens (134 m range)
- Flood: proximity lighting, 174 lumens (38 m range)
- Spot + Flood: combined lighting, 329 lumens (133 m range)

Benefits:

Peli™ 3415M0 torches are particularly popular with maintenance crews, firefighters and high-risk industrial sectors. These ATEX zone 0 Peli™ torches are intervention tools featuring a dual LED spotlight. Thanks to their pivoting head and integrated magnet, they rank among the most effective protective accessories on the market.

Standards and certification :

- **ATEX certification**: CE Ex II 1 G Ex ia op is IIC T4 Ga (gas)
- **Manufacturer reference**: 0341500303-241E
- **Customs code**: 85131000
- **EAN**: 19428156893